

## Slurry Cultivators

### IN-Terra



#### Technical specifications

	3000	4000	5000	6000	7000
Attachment	Three-point linkage, Cat. 2 and 3, bolts Cat. 3 and 4				
Working width	3 000 mm	4 500 mm	5 250 mm	6 000 mm	6 750 mm
Working depth	200 mm				
Working speed	Max. 15 km/h				
Total length	2 800 mm				
Transport width	3 000 mm				
Transport height	1 900 mm	2 900 mm	3 000 mm	3 500 mm	3 800 mm
Weight	1 700 kg	2 600 kg	2 750 kg	3 050 kg	3 200 kg
Hydraulic devices (double-acting)	1	2	2	2	2
	Increases with additional equipment				
Electrics	12 V system with 7-pin plug, lighting (German regulation)				
Wheels	Tyres 195/50 B 10 TL				
Quantity	2	4	4	4	4

**The country needs clever technology**

**Lomma Sachsen GmbH**  
 Mertitzer Straße 6  
 D-01623 Lommatzsch  
 Telefon: +49-35241 57-0  
 mail@lomma-sachsen.de  
 www.lomma-sachsen.de

## Slurry application (direct injection)

	3000	4000	5000	6000	7000
Slurry hoses	highly flexible, rubber-steel fabric, UV resistant				
Slurry outlets	9	13	15	17	19
	Rear: The outer outlets are prepared for the connection of 3 hoses. All others: The inner outlets are prepared for the connection of 2 hoses.				

## Tines

	3000	4000	5000	6000	7000
Material	Hardened steel				
Quantity	9	13	15	17	19
Line distance	375 mm	375 mm	375 mm	375 mm	375 mm
Row distance	750 mm				
Tine distance	900 mm				
Tines unit	Quick-change tines 50 mm on quick-change system				

## Implements

	3000	4000	5000	6000	7000
Drag tines	With single suspension				
Quantity	10	14	16	18	20
Bar roller Ø 520 mm	•	•	•	•	•
Other Implements	On demand				

## Additional equipment

	3000	4000	5000	6000	7000
Drag tines (individual or set)	•	•	•	•	•
Tines unit	Various tine sizes are possible due to the universal quick-change system				
Reinforced tines	Reinforced with carbide				
Working width	Modular extension for larger versions				—
Pneumatic drip stop	•	•	•	•	•