

Subsoiler Land-Crusher



Technical specifications

	1800 – 4500
Attachment	Three-point linkage, Cat. 2, 3 or 3, 4
Working width	1 800 mm bis 4 500 mm
Working depth	up to 550 mm
Working speed	6 to 8 km/h
Length	1 600 mm
Transport width	2 990 mm
Weight	550 kg to 1 400 kg
Hydraulic devices (double-acting)	1 2 (above 3 000 mm working width)
Electrics	12V system with 7-pin plug, lighting (German regulation)

The country needs clever technology

Lomma Sachsen GmbH

Mertitzer Straße 6

D-01623 Lommatzsch

Telefon: +49-35241 57-0

mail@lomma-sachsen.de

www.lomma-sachsen.de

Tine system

	1800 – 4500
Tines	Sandwich tines made of Hardox
Quantity	2 to 9 – on demand
Line distance	450-1 000 mm – on demand
Front tine	Heavy cultivator blades with 40 mm narrow prefix blades
Tine distance	On demand – free selectable
Stone protection	Hydraulically, individual adjustable Single tines can be switched on / off Sideways evasive

Implements

	1800 – 4500
Bar roller	Ø 450 mm
Spring band roller	Ø 560 mm
Disc row	Ø 510 mm
Sectional disc row	Ø 510 mm
Other implements	on demand

Additional equipment

	1800 – 4500
Disc-coulter	Optional, replaces front tines
Support wheels	Optional, 2, tyre or steel
Lighting	Optional
Drain-bolt	Ø 60 mm