

Slurry Tanker

Two-axle slurry tanker



Technical specifications

	16000	18000
Dimensions	length x width x height	
	8950 x 3000 x 3600 mm	9600 x 3000 x 3600 mm
Registered total weight	24000 kg	24000 kg
Basic weight	17200 kg	17700 kg
Chassis	Tandem chassis with parabolic suspension BPW axles (self-steering or positive steering axle) Tyres BKT 850/50-30,5	
Tank	Capacity: 16000 to 18000 litres 14000 litres on demand "Börger" rotary piston pump Self-supporting tank, fully galvanized / in RAL colours Electronic control system Lateral 8-inch suction arm Central lubrication system: manually in the front with stainless steel holder Attachments: three or four-point lifting unit for heavy attachment equipment	
Speed	40 km/h	
Hydraulic devices (double-acting)	2	
Electrics	12V system with 7-pin plug, lighting (German regulation) Control panel	
Air brake system	Dual-line air brake system	

The country needs clever technology

Lomma Sachsen GmbH

Mertitzer Straße 6

D-01623 Lommatzsch

Telefon: +49-35241 57-0

mail@lomma-sachsen.de

www.lomma-sachsen.de

Additional equipment

	16000	18000
Tank	"Vogelsang" 8" filling accelerator Application accelerator on the attachment equipment, rear, 8" Suction point on the tank, left and/or right side with a 6" quick fastener	
Axles	Self-steering or positive steering	