

Vario-Snow-Plow

also for maize levelling



Technical specifications

	2900	3200	3350	3500
Attachment	See supplementary equipment			
Snow-clearing path				
Parallel position	2 900 mm	3 200 mm	3 350 mm	3 500 mm
Wedge/Tilted position	2 600 mm	2 870 mm	3 000 mm	3 350 mm
Total length (incl. attachment)	800 to 1 800 mm (depends on position)			
Shield height (transport height)	ca. 850 mm			
Weight (incl. headstock)	ca. 520 kg	ca. 570 kg	ca. 580 kg	ca. 590 kg
Hydraulic devices (double-acting)	1			
Electrics	12V on-board power system for positioning lights and adjustment, lighting (German regulation)			
Lateral inclination angle	± 27,5 degrees			
Horizontal inclination angle	± 6 degrees			
Operating positions	Parallel-, left-, right-, wedge- and V-position			

Country requires clever technology

Lomma Sachsen GmbH
 Mertitzer Straße 6
 D-01623 Lommatzsch
 Telefon: +49-35241 57-0
 mail@lomma-sachsen.de
 www.lomma-sachsen.de

Building up

	2900	3200	3350	3500
Shield	Divided and durable steel sheet blade with deflector			
Overload protection	Headstock with suspended scraper bar and shear bolt protection			
Operating position	Can be chosen by the driver via the control unit			
Scraper bar	Optionally 25, 30 or 40 mm rubber or polyurethane with/without fabric inlay with a shore hardness of 65° to 70°			

Additional equipment

	2900	3200	3350	3500
Lateral support wheels	Continuously adjustable for height control			
Plow wing extensions	Bolted, can be retrofitted at any time			
	—	2x 150 mm	2x 225 mm	2x 300 mm
Variable attachments	Three-point linkage, category 2 Three-point linkage, category 3 Euro-standard socket, category 2 (82 cm) Euro-standard socket, category 3 (102 cm) More on request			

Operating positions: Parallel-, left-, right-, wedge- and V-position

